



INVERSOR ELECTRÓNICOS ONDA SENOIDAL MODIFICADA

Linea IOE - IOE600 - 600W con USB **Inverter Expert**




Características

- Salida USB
- Carcasa de aluminio anodizado para mayor durabilidad y mejor disipación de calor
- Ficha de conexión 12V para vehículo y pinzas de alta resistencia para conexión a batería
- Función de reinicio automático
- Indicadores LED de estado de trabajo e indicadores de falla
- Llave interruptora ON/OFF manual
- Equipo liviano, compacto y fácil de operar
- Alimentación de las cargas directamente desde la salida CA
- Equipado con protecciones que garantizan la protección del equipo y una operación segura

USB **RoHS** **CE** -LVD/EMC **1.5** YEAR LIMITED WARRANTY

AC Output Receptacles(optional)



Especificaciones

Model			IOE-600-12		IOE-600-24
Output	AC Voltage		230V		230V
	AC Voltage Range		220-240V AC		220-240V AC
	AC Regulation	±10%			
	Rated Power	600W			
	Peak Power	1200W			
	Waveform	Modified Sine Wave 			
	Frequency	50/60Hz±3			
	No Load Current Draw	≤ 0.5A			
	Efficiency	≥90%			
	USB	5V 2.1A(optional)			
	LED Indicator	Green for power on, Red for power failure status			
	Cooling fan	Running once connect AC loads / temperature control (optional)			
Input	DC Voltage	12V		24V	
	Voltage Range	9.5~16V DC		19~32V DC	
	DC Connector	600mmDC cable with cigarette lighter plug *1 ea, battery DC cable*2ea			
Protection	Low Voltage Alarm	9.5±0.5V DC		19±1V DC	
	Low Voltage Shutdown	10±0.5V DC		20±1V DC	
	Reset Voltage after L.V.S	11.5~12V		23~24V	
	Overload	Shut off output, auto.reset			
	Over Voltage	15~16V DC		30~32V DC	
	Over Temperature	Shut off output automatically, auto. reset			
	Output Short-circuit	Shut off, auto.reset			
	Reverse Polarity	Fuse burn out			
	Replaceable Fuse	40A		20A	
	Soft Start	Yes,3~5s			
Environment	Earth Leakage	Yes			
	Working Temp.	0~30℃= @ 100% load; 40℃=@50% load			
	Working Humidity	20%~90% RH non-condensing			
	Storage Temp., Humidity	-30~+70℃/-22~+158°F, 10~95%RH			
Safety&EMC	Temp. Coefficient	10%~90% RH			
	Isolation Resistance	-20℃ ~ +50℃			
	EMI Conduction & Radiation	I/P-O/P:100M Ohms/500VDC/25/70%RH			
	EMS Immunity	Compliance to EN55022 chass B, 72/245/CEE, 95/64/CE			
	LVD	Compliance to EN61000-4-2,3			
	E-mark	Compliance to EN60950, EN61558-1-2			
Other	N.W.(g)	1000g			
	Dimension(cm)	22*13.4*5.8cm			
	Packing	Gift box, 16 units/24Kg/Ctn(57.5*32*38.5cm)			
	Output Socket	A, B, C, D, E, F, G optional			

Note: Specification prior to change without notice (If no need USB, pls contact our sales).